

# EVO Pod Tech Specs

## NETWORK

---

- IPv4/IPv6 support
- IGMP(v3), IGMP Snooping, MLD
- VLAN IEEE 802.1q
- QoS: IEEE 802.1p, IPv4/IPv6, MAC, Part and DiffServ-based
- WMM, WRED, WRR, Leaky Bucket Shaper Schedule
- MSTP (Multiple Spanning Tree Protocol)

## WLAN

---

- Wi-Fi Access Point
  - 2.4GHz 11ax: 2x2
  - 5GHz 11az: 4x4 (160MHz)
- 20/40/80/160 MHz channels
- WPS support
- Multi SSIDs
- IAS (Intelligent Airtime Scheduling), Band Steering, Hotspot 2.0

## 802.11AX

---

- UL and DL OFDMA AP & STA support
- 11ac and 11ax MU-MIMO
- 4x Symbol Size
- Target Wake Times (TWT)
- 11ax Range Extension mode
- 1024 QAM

## SMART WI-FI

---

- OpenSync-enabled (Plume Wi-Fi software)
- Smart roaming (AP Steering)
- 802.11 b/g/n/ac/ax
- Band-steering
- ACS (Auto Channel Selection)

## ACCESSORY

---

- 12V / 1.5A Power adaptor
- Ethernet Cable
- User Manual

## MANAGEMENT/DIAGNOSTICS/ CONFIGURATION

---

- WEB/UI(HTTP/HTML), Remote Diagnostics

## COMPLIANCE/CERTIFICATES

---

- RoHS Compliant
- Wi-Fi Alliance

## PHYSICAL INTERFACE

---

- Front Panel
  - LEDs
- Rear Panel
  - 2 x GbE LAN Ports (1 x convertible to WAN)

## FEATURES

---

- Wi-Fi Insight
- Graphical Connection View

## MECHANICAL & ENVIRONMENTAL SPECIFICATION

---

- Operating Temperature: 0°C (32°F) – 40°C (104°F)
- Storage Temperature: -30°C (86°F) – 60°C - 140°F)
- Humidity: 10-90% (Non-condensing)
- Dimensions (W x D x H): 54(7.2)mm x 130mm x 130mm